GEKA® plus automatic hose reel EA15

available now

GEKA® plus automatic hose reel EA15

suspension of the reel

Suitable for drinking water

Automatic roll-up of the hose locks 2x per rotation

With individually positionable hose stopper for different hose sizes (1/2", 5/8", 3/4") Gentle hose guide prevents the hose from jumping off the reel during reeling

Suitable for wall, floor and ceiling mounting

Hose guide on the axle adjustable in three 45° steps

rollers, inlet pipe, locking mechanism (toothed washer, catch, spring, snap ring),

GEKA® plus rotary fitting: stainless steel, hose stopper: black rubber

Operating pressure at +20 °C:Max. 20 bar (hose-dependent)

Temperature range:+4°C to +60°C (hose-dependent)

Dimensions L x W x H cm:......52 (incl. mount) x 45 x 23,5

hoses with an outer diameter of 17 mm

Screws and wall plugs for wall mounting are not included in the scope of delivery **Stainless steel swivelling wall mount 165° incl. connecting screws**

(42.9097.9) and various supply hoses available separately as an accessory



Connection	Male thread
Male thread mm	26,44
Male thread	G3/4
Capacity of 1/2" hose approx. m	25
Capacity of 5/8" hose approx. m	24
Capacity of 3/4" hose approx. m	15
Weight approx. kg	14
PU units	1
Article No.	42.9040.9



Robust stainless steel construction



GEKA® plus rotary fitting and stainless steel pipe



Suitable for wall, floor and ceiling mounting