


GEKA® automatic wall-mounted hose box K25

Advantages / benefits: **Automatic roll-up and comfortable unwinding** of hose without knotting; hose can be locked in any position;
Controlled and safe hose intake (slow retract);
Tool-free adjustable hose stopper;
Robust wall mount: 180° rotatable;
incl. mounting kit (4x dowels, 4x screws and 4x stainless steel washers);
with **anti-drip feature** for **supply hose** thanks to **practical plug-in option;**
Easily removable from the wall bracket;
No unintentional swinging back and forth of the hose box **thanks to Position Plus**
Water hose **phthalate-free**
Fully assembled and ready to use;
Including high quality, robust **push-fit connector system** and **spray nozzle** made from chrome-plated brass;

Operating pressure at +20 °C:..... 8 bar
Temperature range:..... +4 °C to +45 °C
Dimensions L x W x H cm:..... 62 x 26 x 43 (incl. mount)
Scope of delivery: GEKA® plus spray nozzle, light; GEKA® plus hose piece 1/2";
GEKA® plus hose piece 1/2" with water stop; GEKA® plus tap plug G3/4,
15 m hose + 2 m supply hose



| | |
|------------------------------|------------------|
| Hose size | 1/2" |
| Hose ID mm | 12,5 |
| Hose length approx. m | 25 |
| Approx. length supply hose m | 2 |
| PU units | 1 |
| Article No. | 42.8721.9 |




Automatic roll-up




Infinitely variable locking mechanism




Incl. assembly kit and metal mount



Supply hose 2 m




can be adjusted without tools




Incl. push-fit connector system made of metal



Reduces unwanted swinging back and forth



Plug-in option for supply hose



180° rotatable

