

Tank truck couplings TW and accessories, *brass*


Advantage / benefit:..... forged version, excellent strength and fracture resistance as per EN 14420-6 (previously DIN 28450)
 Material:..... brass
 Temperature range: approx. -10 to +65 °C
 Seal: NBR
 Operating pressure: -0.8 to 16 bar
 Area of application: for shell inclusion



Type VK, male connector parts with female thread

Flat sealing with seal ring on threaded side


Female thread in mm	57.29	85.56	110.71
Female thread	G2	G3	G4
Nominal width (NW) mm	50	80	100
PU units	1	1	1
Item no.	17.1221	17.1222	17.1223



Type MK, female connector parts with lever and female thread

Comprising lever lock and crown ring.
 Flat sealing with seal ring on threaded side, moulded seal ring on coupling side

Female thread in mm	57.29	85.56	110.71
Female thread	G2	G3	G4
Nominal width (NW) mm	50	80	100
PU units	1	1	1
Item no.	17.1224	17.1225	17.1226



Hose nozzle with grommet profile and male thread

Male thread in mm	33.25	41.91	47.80	59.61	75.18	87.88	113.03
Male thread	G1	G1¼	G1½	G2	G2½	G3	G4
Hose ID mm	25	32	38	50	63	75	100
Hose size	1"	1¼"	1½"	2"	2½"	3"	4"
Nominal width (NW) mm	25	32	38	50	63	75	100
PU units	1	1	1	1	1	1	1
Item no.	17.1208	17.1209	17.1210	17.1211	17.1212	17.1213	17.1214 *

8



Hose nozzle, smooth with safety collar and male thread

Male thread in mm	33.25	41.91	47.80	59.61	75.18	87.88	113.03
Male thread	G1	G1¼	G1½	G2	G2½	G3	G4
Hose ID mm	25	32	38	50	63	75	100
Hose size	1"	1¼"	1½"	2"	2½"	3"	4"
Nominal width (NW) mm	25	32	38	50	63	75	100
PU units	1	1	1	1	1	1	1
Item no.	17.1201	17.1202	17.1203	17.1204	17.1205	17.1206	12.1277



Hose nozzle, smooth with safety collar and female thread

Female thread in mm	30.93	39.59	45.48	57.29	72.86	85.56
Female thread	G1	G1¼	G1½	G2	G2½	G3
Hose ID mm	25	32	38	50	63	75
Hose size	1"	1¼"	1½"	2"	2½"	3"
Nominal width (NW) mm	25	32	38	50	63	75
PU units	1	1	1	1	1	1
Item no.	17.1215	17.1216	17.1217	17.1218	17.1219	17.1220

*Grommet profile with two ribbed threads