P25SST

40

25

25

12

42.8506.9

GEKA® plus push-fit connector

GEKA® plus P25 and P25SST hose trolleys

Advantage / benefit:robust, powder-coated steel structure

light and easy to handle with ergonomic grip height optimised frame construction for guaranteed secure stand

and easy manoeuvrability

non-slip solid rubber tyres for comfortable transport

accessory rack to hold a nozzle

tool-free installation and disassembly of handle for quick and compact

storage in winter

quick and simple set-up, no additional tools required

with GEKA® plus push-fit connectors, inner and outer

42.8506.9 with 25 m GEKA® plus water hose WS400 1/2", high-quality, robust push-fit system and spray nozzle made from brass + 1.5 m supply hose

P25

50 40

25

25

42.8501.9

Material:frame: powder-coated steel pipe; handrail, tyres: rubber black;

Connection

device mounting, crank handle: plastic green; supply pipe: stainless steel;

GEKA® plus push-fit connectors: brass, chrome-plated

Temperature range:.....+4 to +60 °C (hose-dependent)

Dimensions cm:41 x 99 x 39

Special note:preassembled; spare parts are available on request



P25 - 42.8501.9

P25SST - 42.8506.9



Sturdy steel construction



Practical holder for devices



Simple, tool-free assembly



Non-slip solid rubber tyres for comfortable transport



Ready to use with GEKA® plus push-fit connector

*measured with rubber hoses

