

## GEKA® plus P40 and P40SST hose trolleys

Advantage / benefit: .....**robust, powder-coated steel structure**  
**suitable for drinking water: the water-conducting components**  
**meet the German drinking water ordinance**  
**with eco-friendly powder coating**  
**optimised frame design for guaranteed stability**  
**and easy rolling**  
**pneumatic, non-slip tyres for comfortable rolling**  
**curved supply hose made of stainless steel prevents the hose from kinking**  
**optimal water flow**  
**with GEKA® plus 90° angled rotary fitting, brass, for drinking water**  
**practical holder for devices**  
**42.8505.9 with 25 m GEKA® plus water hose 110 1/2", high-quality, robust**  
**push-fit system and spray nozzle made of brass + 1.5 m supply hose**

Material: .....**frame: powder-coated steel pipe (Ø 20 mm); handrail, pneumatic tyres: rubber black;**  
**device mounting, crank handle: plastic green; supply pipe: stainless steel;**  
**GEKA® plus rotary fitting: brass**

Dimensions cm: .....**52 x 107 x 55**

Special note: .....**preassembled without hose; spare parts are available on request**

	P40	P40SST
Connection male thread to water tap mm	26.44	26.44
<b>Connection male thread to water tap</b>	<b>G3/4</b>	<b>G3/4</b>
Connection male thread at hose outlet mm	26.44	26.44
<b>Connection male thread at hose outlet</b>	<b>G3/4</b>	<b>G3/4</b>
Capacity of 1/2" hose approx. m*	60	60
Capacity of 5/8" hose approx. m*	55	55
Capacity of 3/4" hose approx. m*	40	40
Hose length approx. m	25	25
Tyre pressure max. bar	2.1	2.1
Weight approx. kg	15,5	20,4
Temperature range °C	+4 to +60	+4 to +60
PU units	1	1
<b>Item no.</b>	<b>42.8502.9</b>	<b>42.8505.9</b>



5



Sturdy steel construction



Practical holder  
for devices



Pneumatic tyres  
for comfortable transport



protection against hose kink  
through stainless steel inlet pipe



GEKA® plus angled rotary  
fitting for drinking water

\*measured with rubber hoses

