## GEKA® plus combined watering wand TF metal

GEKA® plus combine	d watering wand TF w	ith watering head	
Advantage / benefit:	rotatable and replaceable ou wand with handle valve	tlet pipe with dirt filter, watering	
Handling:	with locking element for conf	tinuous operation (half and full power)	
Material:	watering head (50.6399.9) a GEKA® plus quick coupling:		
Connection:	GEKA® plus quick coupling suitable for hose sizes from 3/8" to 1½"		
Options:	large selection of waterin on the following pages	g heads, showers and nozzles	
Connection male thread mm	26.44		
Connection male thread	G3/4		
Water flow rate at 3 bar I/min	approx. 32		
Pipe Ø in mm	19 x 1		
Pipe bend	35°		
Pipe length in cm	60		



## **GEKA®** plus pot watering wand metal

51.5330.9

## GEKA® plus pot watering wand without watering head

Covering box units

Item no.

Advantage / benefit:	watering wand with handle valve small push-fit cone with female thread for attaching showers
Handling:	one-hand quick-action valve with <b>locking element for continuous operation</b> (half and full power)
Material:	outlet pipe with cap nut: aluminium; push-fit cone: brass; GEKA® plus quick coupling: brass, chrome-plated
Connection:	push-fit cone with female thread; GEKA® plus quick coupling suitable for hose sizes from 3/8" to 1½"
Use:	for targeted watering of pot plants

Female thread connection	M 11 x 1	
Water flow rate at 3 bar l/min	approx. 30	
Pipe Ø in mm	14 x 1.5	
Pipe bend	35°	
Pipe length in cm	60	
PU units	1	
Covering box units	20	
Item no.	51.5300.9	



6

Irrigation technology GEKA® Main Catalogue 139